#### LIFTS

### **Features**

- Two-layer concealed plate structure, excellent synchronizing performance with the horizontal precision of 1mm
- performance with the horizontal precision of 1mm
  Front wheel turn plate's position is adjustable and rear wheel sliding plate is extended for various vehicle type
- Deployed with rolling jack with small scissor hydraulic lifting and lowering, can be moved back and forth and easy to adjustment tire
- Positioning level's accuracy is adjustable, distance between platforms is adjustable, wheel base in certain scope is adjustable
- Driven by hydraulic cylinder, full-scope mechanical safety locking by locking latch, manual lowering
- Cable rupture safety system ,effectively protects vehicle from overturn
- Four connected steel cables force synchronized movement of the lift, effectively prevent vehicles from sloping

## **Technical Parameters**

Rated load: 4000kg Lifting height: 1850mm Initial height: 220mm Lifting time: ≤60s

Lowering time: ≥20s ≤40s Max drive-on width: 3045mm Platform length: 4240mm Platform width: 500mm Overall width: 3445mm Overall height: 2172mm Motor power: 2.2kw

Motor voltage: 3 phase/380v or Single phase/220V

#### **Secondary lift**

Platform length:915~1450mm

Platform width:215mm

Lifting time:≤ 45s

Rated load:2000kg

Lifting height:450mm

Working noise:≤ 70dB (A)

Working oil pressure:16MPa

Working air pressure:0.5~0.7 MPa

# **Configuration Instructions**

		Basic	CE Standard
Drive on ramp assembly	508X1060mm	•	•
Unlocking device	Manual lowering device	•	•
Power unit	Domestic 2.2kW 12L	•	•
Secondary lift	2 ton	•	•
Turntable		•	•
Side slip plate		•	•
Safety device	Control box , cylimit limit device, Emergency lowering device, CE-STOP, loose rope forced balance system		•
Color	Launch red, Launch grey, Volkswagen blue, Hyundai blue, GM blue (Buick blue)	•	•
Warranty	1year	•	•



- Cylinder travel limit device effectively protects cylinder and extends its lifespan
- Electric controlled lifting and lowering type is optional
- The installation position of turntable and side slip plate can be moved backwards and forwards
- Applicable for vehicles with different wheel base
- CE certificated

