



PARAMETERS	Standard mode		Mode		Luxury mode	
	CCH-101	CCH-102	CCH-201	CCH-301	CCH-401	CCH-402
Overall dimension (m)	7.0*5.3*3.5	8.3*5.5*3.5	7.0*5.3*3.5	7.0*5.3*3.5	7.0*5.3*3.5	15.2*6.6*5.0
inner dimension (m)	6.9*3.9*2.7	8.2*4.0*3.1	6.9*3.9*2.7	6.9*3.9*2.7	6.9*3.9*2.7	15.0*5.0*4.4
Width of door for entrance of vehicle (m)	3.0	3.0	3.0	3.0	3.0	4.0
Height of door for entrance of vehicle (m)	2.7	3.1	2.7	2.7	2.7	4.5
steel plate thickness(mm)	0.326	0.326	0.326	0.426	0.426	0.476
filtrated area(m ²)	20	25	20	20	20	49
Air flow volume (m ³ /h)	21000	36000	22000	25000	25000	72000
Air velocity within booth (m/s)	0.25~0.35	0.25~0.35	0.25~0.35	0.3~0.5	0.3~0.5	0.3~0.5
Ventilation times(times/hr)	265	352	265	332	332	264
Working temperature(°C)	60~80	60~80	60~80	60~80	60~80	60~80
Oil consumption (kg/set)	6~8	9~10	6~8	6~8	6~8	18~30
insulation Material of wall panel	PE	PE	PE	PE	Rock wool	PE
Power(kw)	9	12.5	13.5	17	25	46
Main blower	One unit 7.5 KW European style professional blowers	One unit 11KW European style professional blowers	One unit 7.5KW European style professional blowers; and one unit 5.5KW standard blower	One unit 7.5KW European style professional blowers, and one unit 7.5KW standard blower	One unit 11KW European style professional blowers, and one unit 11KW standard blower	One unit 11KW European style professional blowers, and one unit 11KW standard blower
environmental protection device	no	no	no	yes	yes	no
Nether lighting (side wall)	Equipped with 8 sets	Equipped with 10 sets	Equipped with 8 sets	Equipped with 8 sets	Equipped with 8 sets	Equipped with 20 sets