"The Legendary leader of Automotive Equipments"

ACMAS601+ A/C SERVICE STATION

Model No: ACMAS601+



DaTo ACMAS601+ is an ideal option for workshops that have requirements of handling both R-134a and HFO-1234yf refrigerants. The loss of refrigerant is minimized to less than 50 gram at shifting from one refrigerant to another, and deep internal evacuation ensures zero cross contamination between two refrigerants. The machine is equipped with 2 refrigerant tanks, which saves the operators' time of replacing tanks.




Functions

- Tank fill
- Recovery
- Oil injection
- Charge
- Fully automatic



Multi-Languages





"The Legendary leader of Automotive Equipments"

Specification

- Input power:AC220V±10%~50/60Hz,or AC110V±10%~60Hz
- 7" Touch screen display
- Compressor power:3/8HP
- Hand valves free
- Recovery rate:≥95%
- Average gas state refrigerant recovery speed (through charge/suction port):250g/min
- Vacuum pump capacity:60L/min,non-sparkle
- Accuracy of gas cylinder load cell:±10g
- New/used oil bottle capacity: 250ml/400ml
- Max. Pressure: 20bar
- Charge speed: 2Kg/Min(max.)
- High pressure gauge range: -1 bar~ 30bar
- Low pressure gauge range: -1bar~ 16bar
- A/C database included, free update through USB port
- Dual tank equipped
- Automatic service reminding
- Loss of refrigerant during refrigerant change is minimized