

DaTo

"The Legendary leader of Automotive Equipments"

ACMAS702+ A/C SERVICE STATION (ONE MACHINE FOR BOTH R134A AND R1234YF)

Specification

Input power : AC220V+ 10% - 50/60Hz, or AC110V+ 10% - 60Hz

Hand valves free

Compressor power : 3/8 HP

Average gas state refrigerant recovery speed (through charge/suction port) : 0.25Kg / min

Recovery rate : 96%

Vaccum pump capacity : 60L / min, non-sparkle

Accuracy of gas cylinder load cell : +10g

AC database included, update throught USB port

New oil bottle capacity : 250ml

Used oil bottle capacity : 400ml

Max. pressure : 20bar

Charge speed : 2kg/min (max)

LCD display : 4.3inch TFT full color

High pressure guage range; 1-4bar

Low pressure guage range : 1-22bar

Dual condensors and cooling fans (one for R134a, one for HFO-12354yf)

Capacity of dual gas cylinders : 10kg(one for R134a, one for HFO-1234yf)

Dimension: Package : 720*670*1190mm Unpacked:633*678*1040mm

Model No : ACMAS702+



Dual Tank Equipped



Features

- Fully automatic.
- Amply database.
- Hand valves free.
- Dual tank equipped.
- Automatic service reminding.
- Loss of refrigerant during refrigerant change is minimized.
- Machine pipeline complete evacuation for refrigerant change.

Functions

- Recovery
- Vaccum
- Oil injection
- Charge
- Fully automatic



Multi-Languages



Easy Operation



Equipment Self-Diagnosis