

"The Legendary leader of Automotive Equipments"

LJCB - TWO POST BASE PLATE LIFT


DaTo Lift introduces a revolutionary double Lock system installed in both the columns. This lift manufactured with high quality manufacturing standards and added with the advanced features like super symmetric arms, single- point safety release etc. it is a solution for the low ceiling garages, where the height lesser than 3 to 3.5 meter. DaTo lift is equiped with the Self lubricating polyethylene slider.

Features

- Base plate lift used on the Low Roof garage, where the height of the roof is not sufficient to install a Clear floor lift.
- Dual hydraulic Chain Lifting system.
- Arm suitable for Quick droping Extensions and Other lifting accessories.
- Three stage Short arms and Three stage Long arms provide asymmetric lifting of vans and off-road Vehicles.
- Mechanical safety latch with Automatic solenoid locks and Microprocessor controlled automatic lifting and unlocking function.
- Self-Controlled Lowering Speed.
- HighlyQuality powder coating for Durability and Elegant appearance.

Specifications

Parameters	LJCB2040A	LJCB2045A	LJCB2050A
Power Supply	220/380V	220/380V	220/380V
Motor Power	2.2KW / 3HP	2.2KW / 3HP	2.2KW / 3HP
Capacity	4 Ton	4.5 Ton	5 Ton
Lifting Height	1830/1890mm	1830/1890mm	1830/1890mm
Pass Width	2438mm	2800mm	2800mm
Lift Height	2878mm	2878mm	2878mm
Lift Width	3440mm	3440mm	3440mm
Min Lifting Height	90mm	90mm	90mm
Drive	Electrical Hydraulic	Electrical Hydraulic	Electrical Hydraulic



Model No: LJCB 2045A





Full Automatic Control Panel



Arm Locking Mechanism



Limit Switch



Lock Solenoid

