

DaTo

"The Legendary leader of Automotive Equipments"

PBBAF125 - PAINT BOOTH



Specification

Product Name		Spray booth
Model No.		GL8 (Chinese standard)
External Size		8.7 X 5.63 X 4.23(m)
Internal Size		8.6 X 4.0 X 3.4 (m)
Wall Panel	Color	White
	material	EPS, Thickness: 50mm
	Color steel	Thickness: 0.426mm with metal edge cover
Front Door	Enter Size	3 X 3.35(m)
	Structure	3 folded sheet metal process without frame
	Color	Orange
		White (Front horizontal panel and front vertical panels)
Safe Door		White; 1870 X 650 (mm), 1 piece in the side wall, With pressure lock
Light System	Top light	(2) sides x (6) sets x (4) pcs, (40) W/ piece
	Side light	No
Generator	Color	White, Iron frame, powdered
	Burner	Italy Riello G20S
	Intake Fan	(1 set of 11kw) with M style pre-filter
	exhaust fan	No
	Fan capacity	(35000) / M ³ /h
	Duct	With 5m exhaust duct and without intake duct
	Chimney duct	5m straight chimney and 2 small bends
Motor Voltage	Motor Voltage	380V/50HZ/3PH (Other voltage for option, but RMB1100 added)
	Control box	Import components; Motor Y/Δ start ; Without pressure meter
Total Power		(13) kw
Basement	Floor	(3) rows of veins plates, (2) rows of grids
	Floor filter	Imported (2 rows/set)
	Ramps	2 pcs of veins plates style ramps
Filter frame on the ceiling	Top filter	Imported 5 pcs/set
	Structure	Hinge installed iron welded, powdered
Environmental system		No (Active carbon system for option)