

DIGD603 – GDI/PIEZO INJECTOR CLEANER ULTRASONIC CLEANER



On-Vehicle
Cleaning



Reverse
Flush



Leakage
Test



Automatic
Test



uniformity/
Sprayability Test



Injecting
Flow Test



Ultrasonic
Cleaning



Smart touch
Screen



APPLICATION

1. 12V Conventional injector
2. 75V GDI injector
3. 125V Piezo injector

FEATURES

1. Idle testing
2. Middle speed testing
3. High speed testing
4. Leak testing
5. Accelerated testing
6. Manual Testing
7. Auto Model
8. Simulation Testing
9. Circulation Testing



Dimensions (W*D*H)	400mm*320mm*450mm
Weight	18kg
Power supply	85-132Vac/170-264Vac 47-63HZ
Tank capacity	2.4L
Test tube capacity	120cc
Ultrasonic frequency	38-39KHz 100W
Rotate speed	0~9975r/min, step:25r/min
Pulse width	0~30ms. Step: 0.1ms
Count	0-9975, step: 25times
Pressure of fuel system	0~8bar (can be adjusted)
Test cylinder	4 or 6cylinder

FUNCTIONS

1. Working modes test
2. Injecting volume test
3. Leakage test
4. Uniformity test
5. Sprayability test
6. Ultrasonic cleaning
7. Supports full GDI injectors
8. Supports Piezo injectors
9. Full test for low resistance injectors
10. Drain the testing liquids by Solenoid, no hand function

