



Product Description

DaTo Super is a high performance motor oil from fully synthetic blend tuned for use in all recreational 4-cycle engines. It is formulated with robust dispersant/detergent additives with high performance synthetic base oils that effectively neutralize the high levels of acids and combustion by products inside the engines.

Benefits

DaTo Super provides the following benefits when used as recommended:

- Helps to preserve engine power and ensures productivity.
- Reduces the oil consumption.
- Keeps engine clean for oil efficiency and reduced maintenance.
- Helps cut maintenance costs.
- Excellent oil transmissions.
- Superior wear protections.

Application

It is designed for use in 4 – stroke ATV, UTV, Snow mobile and other power sports engines and in transmissions found in 2 or 4 –stroke applications.

It is recommended to use in Polaris, Honda, Yamaha, Ski-Doo, Can-Am(Bambadier),Suzuki, Kawasaki and Arctic Cat.

Properties

It is a high performance lubricant designed for use in transmissions, final drives, hydraulic systems requiring a fluid meeting Caterpillar TO-4 or Allison C4 requirements. This is designed for both newly developed and older model drive train components.

Typical Characteristics

Super	10W40	Credentials & Specifications
API Grade	SN	API: SN
Specific Gravity @ 15°C	0.8667	NMMA: FC-W(CC)
Flash Point, °C	235	JASO: MA
Pour Point, °C	-48	
Viscosity at 40, °C, cSt	90	
Viscosity at 100, °C, cSt	14.5	
Viscosity at Index	175	
Total Base No., Min.	9.5	
CCS Viscosity cP @-25 °C	6100	

Typical physical characteristics of DaTo Lubricants are given in the table. These are intended as a guide to the industry and are not necessarily manufacturing or marketing specifications.

Healthy and Safety

Detailed health and safety information for this product is provided in a Material Safety Sheet which is available upon request from your DaTo Lubricants sales Office, or via the internet on www.datolube.com